

Customer Information	
*Required Information	
Contact Name*	
Company*	
Address (Street No.)	Postal Code
City	Country
E-mail*	
Contact Number*	

Application	Inline	Portable
Description*	Short Description	

Pipe/ Duct Details		
Pipe/Duct Material	MS SS-316	CS Other
Type	Pipe	Duct
Dimension*		x

Process Parameters			
Medium*	Compressed Air Flue Gas Natural Gas	Process Gas Bio Gas Other	
Condition of Medium*	Dry	Wet	Corrosive
Medium composition	% Main components % Dust Concentration	% Moisture % Other	
Density			
Flow Range*	Minimum	Operating	Maximum

N* refers to 0°C, 1.01325 bar; S* refers to 20°C, 1.01325 bar

Pressure*	Minimum	Operating	Maximum
Temperature*	Minimum	Operating	Maximum
Relative Humidity	% OR	Atmospheric Dew Point	
Sensor Area Classification	Weather Proof IP65 Others	Water proof IP67	
Available Straight Length			

Signal Evaluation Unit Configuration

Power Supply*	18-36 VDC OR Other	100-265 VAC@50Hz	
Outputs	0/4-20mADC OR Optocoupler Impulse output OR	0-10VDC 1 NO / NC Relay contact @ 250VAC / 6A	
Communication Protocol	RS 232 OR Other	RS 485 Modbus	
Enclosure Area Classification	IP65 (ABS Plastic) Other	IP65 (Aluminium Diecast)	

Comments/Additional Requirements

LEOMI INSTRUMENTS PVT. LTD.

E-17/5, Electronic GIDC, Sector-26, Gandhinagar-382027, Gujarat, INDIA.

+91 79 23287899, +91 90547 50586 ✉ sales@leomi.in 🌐 www.leomi.in